

Case: test_2

Initial stage: make a working directory, for example /tmp/test_2

Note: when no precision is given, let the default values.

1 Creation of the case

HOMARD menu, tab « New case »

In this new window:

- Directory: select the working directory created above
- Mesh: select the file test_2.00.med
- Check the option « Discrete Boundary »

The list « Discrete Boundary » is empty. Click New.

In this new window:

- Name: modify the default value by giving internal_boundary
- Mesh: select the file test_2.fr.med

Validate the creation of the boundary by the button « OK ». Back in the window for the creation of a case, the boundary internal_boundary is added to the list of the discrete boundaries.

Validate the creation of the case by the button « OK ».

The case Case_1 and the initial iteration PLAQUE_0 are included in the object browser. In the SMESH module, the meshes PLAQUE_0 and plaque are included with an icon « Imported mesh ». A new tab Boundaries is added to the object browser and contains the boundary internal_boundary.

2 The first iteration

Creation of a new iteration

Select with the mouse (left) the initial iteration PLAQUE_0, then (right) select the tab « Next iteration »

In this new window:

- Mesh n+1: modify the default value by giving PLAQUE_1
- Click « Hypothesis / New »

Creation of the first hypothesis

In this new window:

- Check the button « Filtering with groups »

In the list of the proposed groups, hold « BANDE » and « EG ».

Validate the selection of the groups by the button « OK ». Back to the window of creation of a hypothesis.

Validate the creation of the hypothesis by the button « OK ». The window of the creation of a new iteration is back. The hypothesis Hypo_1 is included in the list of hypotheses

Validation of the iteration

Validate the creation of the iteration by the button « OK ». Under the case Case_1, the iteration Iter_1 is added to the object browser with an icon meaning that the iteration is not computed. The hypothesis Hypo_1 is added under the tab Hypotheses in the object browser.

Compute the iteration

With the mouse, select the iteration Iter_1, then select the tab « Compute and publish ».

The icon of the iteration Iter_1 means that the iteration is computed. Under the iteration, the object

browser grew rich of three files: both first ones are files text, being able to be displayed by the choice « Show file »; the third is the file med, containing the produced mesh, for information.
In the module SMESH, the mesh `PLAQUE_1` appears with the icon of a produced mesh.

3 The second iteration

Select with the mouse the iteration `Iter_1`, then select the tab « Next iteration »

In this new window:

- Mesh n+1: modify the default value by giving `PLAQUE_2`

Validate the creation of the iteration by the button « OK ». Under the case `Case_1`, the iteration `Iter_2` is added to the object browser.

With the mouse, select the iteration `Iter_2`, then select the tab « Compute and publish ». The same comments as for `Iter1`.

4 The third iteration

Creation of a new iteration

Select with the mouse the iteration `Iter_2`, then select the tab « Next iteration »

In this new window:

- Mesh n+1: modify the default value by giving `PLAQUE_3`
- Click « Hypothesis / New »

Creation of a new hypothesis

In this new window:

- Click the option « Filtering with groups »

In the list of the proposed groups, hold « `M_D` ».

Validate the selection of the groups by the button « OK ». The window of the creation of a new hypothesis is back.

Validate the creation of the hypothesis by the button « OK ». The window of the creation of a new iteration is back. The hypothesis `Hypo_2` is included in the list of hypotheses and is selected.

Validation of the iteration

Validate the creation of the iteration by the button « OK ». Under the case `Case_1`, the iteration `Iter_3` is added to the object browser with an icon meaning that the iteration is not computed. The hypothesis `Hypo_2` is added under the tab Hypotheses in the object browser.

Compute the iteration

With the mouse, select the iteration `Iter_3`, then select the tab « Compute and publish ». The same comments as for `Iter1`.

5 Controls

Set apart date, the file that is produced in the working directory I03/apad.03.bilan must be identical to the file test_2.apad.03.bilan which is in the reference directory of the cases-tests.

If a dump python is made, the produced file must be similar to the file test_2.py which is in the reference directory of the cases-tests.

State of the window Salome at the end:

